



United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/651,849	08/31/2000	Sarath Kumar	16-11-30-5	4424
75	590 01/23/2004		EXAMINER	
Harness Dickey & Pierce PLC			D AGOSTA, STEPHEN M	
P O Box 8910 Reston, VA 20195			ART UNIT	PAPER NUMBER
2.00.00.0			2683	8
			DATE MAILED: 01/23/200	4
			<u> </u>	samon 1

Please find below and/or attached an Office communication concerning this application or proceeding.



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEWARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Vignina 22313-1450 www.uspto.gov

APPLICATION NO. FILING DATE FIRST NAMED INVENTOR ATTORNEY DOCKET NO. CONFIRMATION NO. 09/651,849 08/31/2000 16-11-30-5 4424 Sarath Kumar

7590

09/05/2003

Harness Dickey & Pierce PLC P O Box 910 Reston, VA 20195

EXAMINER

D AGOSTA, STEPHEN M ART UNIT PAPER NUMBER

DATE MAILED: 09/05/2003

Please find below and/or attached an Office communication concerning this application or proceeding.

						
	Application No.	Applicant(s)				
	09/651,849	KUMAR ET AL.				
Office Action Summary	Examiner	Art Unit				
	Stephen M. D'Agosta	2683				
The MAILING DATE of this communication appeared for Reply	ppears on the cover sheet with	the correspondence address				
A SHORTENED STATUTORY PERIOD FOR REP THE MAILING DATE OF THIS COMMUNICATION - Extensions of time may be available under the provisions of 37 CFR 1 after SIX (6) MONTHS from the mailing date of this communication. - If the period for reply specified above is less than thirty (30) days, a re - If NO period for reply is specified above, the maximum statutory perio - Failure to reply within the set or extended period for reply will, by statu - Any reply received by the Office later than three months after the mail earned patent term adjustment. See 37 CFR 1.704(b). Status	I. 1.136(a). In no event, however, may a reply sply within the statutory minimum of thirty (3' d will apply and will expire SIX (6) MONTHS tte, cause the application to become ABANI	be timely filed 0) days will be considered timely. 6 from the mailing date of this communication. DONED (35 U.S.C. § 133).				
1)⊠ Responsive to communication(s) filed on 22	2 August 2003 .					
,—	This action is non-final.					
3) Since this application is in condition for allow closed in accordance with the practice under Disposition of Claims						
4)⊠ Claim(s) <u>1-29</u> is/are pending in the application	on.					
4a) Of the above claim(s) is/are withdrawn from consideration.						
5) Claim(s) is/are allowed.						
6)⊠ Claim(s) <u>1-29</u> is/are rejected.						
7) Claim(s) is/are objected to.						
8) Claim(s) are subject to restriction and	or election requirement.					
Application Papers						
9) The specification is objected to by the Examir						
10) The drawing(s) filed on is/are: a) acc						
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).						
11) The proposed drawing correction filed on is: a) approved b) disapproved by the Examiner. If approved, corrected drawings are required in reply to this Office action.						
12) The oath or declaration is objected to by the E	• •					
Priority under 35 U.S.C. §§ 119 and 120	EXAMINOT.					
13) Acknowledgment is made of a claim for forei	an priority under 35 H S C & 1	19(a)-(d) or (f)				
a) ☐ All b) ☐ Some * c) ☐ None of:	gir priority under 55 0.5.5. g 1	13(2)-(3) 31 (1).				
	nts have been received					
 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No 						
3. Copies of the certified copies of the pr						
application from the International E * See the attached detailed Office action for a lie	Bureau (PCT Rule 17.2(a)).	_				
14) Acknowledgment is made of a claim for domes	stic priority under 35 U.S.C. § 1	119(e) (to a provisional application).				
 a) ☐ The translation of the foreign language p 15)☐ Acknowledgment is made of a claim for dome 	• •					
Attachment(s)						
 Notice of References Cited (PTO-892) Notice of Draftsperson's Patent Drawing Review (PTO-948) Information Disclosure Statement(s) (PTO-1449) Paper No(s) 	5) Notice of Info	nmary (PTO-413) Paper No(s) rmal Patent Application (PTO-152)				

Application/Control Number: 09/651,849 Page 2

Art Unit: 2683

DETAILED ACTION

Response to Arguments

Applicant's arguments filed 8-22-03 have been fully considered but they are not persuasive:

- 1. The USC 112 rejection for claim 29 has been overcome based on applicant's amendment to the claim (no depends on claim 28).
- 2. The applicant argues (for independent claims 1 and 24) that the prior art cited does not disclose a lookup table such that an index into the lookup table used in retrieving a scale factor is a function of a ratio between energy components of a wireless signal. The examiner disagrees firstly, the "stored data curve" can be used as a "table" to retrieve values based on the ordinate and abscissa values selected which reads on a table AND indexes can be used to speed the process of finding/determining a needed data value.

Ling teaches computing energy per data symbol (C10, L59-60 and pilot symbol energy (C14, L14-15), Sampath teaches β which can be shown to be a ratio of E_p/E_d by rearranging the equation on page 2, top of left column (eg. $E_p = \beta E_d$), Jalloul teaches the calculation of a "pilot to data power ratio" (C5, L26-37) and Holtzman teaches calculating a ratio between the energy of the pilot symbols and the traffic/data channel's energy (C9, L44-46). It would have been obvious to one skilled in the art at the time of the invention to modify Ling, such that the scale factor is a ratio between energy components, to provide means for correct demodulation (using LLR) based upon a comparison of the energy components of the wireless signal.

3. The examiner stands on his original rejection (although claims 1 and 17 have been modified to add the above language to reject the amendments regarding use of a lookup table such that an index into the lookup table is used.

Art Unit: 2683

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

<u>Claims 1-28 29</u> rejected under 35 U.S.C. 103(a) as being unpatentable over Ling et al. US Patent 6,377,607 in view of Sampath & Kumar VTC Conference 9/1999, Jalloul et al. US Patent 6,192,040 and Holtzman US Patent 6,393,257 (hereafter Ling, Sampath, Jalloul and Holtzman).

As per claim 1, Ling teaches a wireless receiver comprising:

A receiver for receiving a wireless signal (C1, L8-13)

A demodulator for generating a log-likelihood ratio (C2, L50-67 to C3, L1-52) as a function of a scale factor wherein the scale factor is a function of a ratio (abstract, teaches scaling LLR ratio scaling factor as does C4, L37-67 teaches a LLR scaling factor using SIR's) **but is silent on** between energy components of the wireless signal and a lookup table with an index used to retrieve the scale factor.

Ling does teach computing energy per data symbol (\bar{E}_s : C10, L59-60) and pilot symbol energy (E_p : C14, L14-15).

Sampath teaches β which can be shown to be a ratio of E_p/E_d by rearranging the equation on page 2, top of left column (eg. $E_p = \beta E_d$).

Jalloul teaches the calculation of a "pilot to data power ratio" (C5, L26-37).

Holtzman teaches calculating a ratio between the energy of the pilot symbols and the traffic/data channel's energy (C9, L44-46) and a stored data curve/plot which reads on a lookup table (C11, L50-56).

It would have been obvious to one skilled in the art at the time of the invention to modify Ling, such that the scale factor is a ratio between energy components, to provide

Art Unit: 2683

means for correct demodulation (using LLR) based upon a comparison of the energy components of the wireless signal.

As per **claim 2**, Ling teaches claim 1 further comprising a processor for determining the scale factor (figure 5 and C8, L55-61 teaches a circuit/processor for computing S/I and LLR).

As per **claim 3**, Ling teaches claim 2 wherein the scale factor is determined independently of relative strengths and number of mulitpaths in the received wireless signal (C4, L37-67 teaches computing the LLR scaling factor which is independent of relative strengths and number of multipaths since the equation does not show variables for these components).

As per **claim 4**, Ling teaches claim 1 further comprising a processor for determining scale factor as a function of ration between energy components of the wireless signal (see claim 1), a noise variance in received data symbols (C4, L22-27) **but is silent on** a noise variance in received pilot symbols.

Holtzman teaches calculation of the energy per symbol of the traffic channel and determines the estimate of the noise variance (C9, L60-63). Holtzman also teaches (in step 608 of figure 6) the signal and noise estimator estimates the ratio of the energy of the pilot versus the energy of the symbol AND (in step 610) Ep/Es is calculated (C9, L64-67 to C10, L1-7). Holtzman goes on to disclose that other functions and methods may be performed by the signal/noise estimator and control process (C10, L8-16) which reads on calculating a noise variance in received pilot symbols.

It would have been obvious to one skilled in the art at the time of the invention to modify Ling, such that noise variance in received pilot symbols is used, to provide means for incorporating the pilot symbol noise variance into the LLR function.

As per claim 5, Ling teaches claim 4 wherein the scale factor is determined independently of relative strengths and number of mulitpaths in the received wireless signal (C4, L37-67 teaches computing the LLR scaling factor which is independent of relative strengths and number of multipaths since the equation does not show variables for these components).

Art Unit: 2683

As per claim 6, Ling teaches claim 1 and a lookup table (figure 8, #140) but is silent on comprising memory for lookup table storing the scale factor.

Holtzman teaches using a stored data curve (or plot) which reads on a lookup table (C11, L50-56).

It would have been obvious to one skilled in the art at the time of the invention to modify Ling, such that a lookup table is used for storing scale factor, to provide quicker means of finding the correct/optimal scale factor (ie. lookup versus finding data on a data curve/plot).

As per **claim 7**, Ling teaches claim 6 wherein the function is a square root of the ration between the energy components of the signal (C14, L4-18 teaches a square root function of Es/Ep and "k" is interpreted to be the scale factor of the LLR).

As per **claim 8**, Ling teaches claim 1 **but is silent on** wherein the received signal comprises pilot symbols and data symbols and the ratio between energy components is a ratio between transmitted energy per pilot symbol to a transmitted energy per data symbol.

Ling does teach computing energy per data symbol (\bar{E}_s : C10, L59-60) and pilot symbol energy (\bar{E}_p : C14, L14-15).

Sampath and Kumar teach β which can be shown to be a ratio of E_p/E_d by rearranging the equation on page 2 (eg. $E_p = \beta E_d$).

Jalloul teaches the calculation of a "pilot to data power ratio" (C5, L26-37).

Holtzman teaches calculating a ratio between the energy of the pilot symbols and the traffic/data channel's energy (C9, L44-46).

It would have been obvious to one skilled in the art at the time of the invention to modify Ling, such that the scale factor is a ratio between energy components, to provide means for correct demodulation (using LLR) based upon a comparison of the energy components of the wireless signal.

As per **claim 9**, Ling teaches claim 1 wherein the receiver comprises a demultiplexer for providing a data signal (eg. data), control signal (eg. pilot) and the ratio (figures 2 and 4, shows a receiver with pilot, control and data signals being sent to the "C/I estimation and LLR computation" processor).



Art Unit: 2683

As per **claim 10**, Ling teaches claim 9 wherein the receiver comprises a control signal detector for recovering from the control signal a value for the ratio between the energy per pilot symbol to the energy per data symbol (figures 2 and 4 shows pilot, control and data signals being passed to the "C/I estimation and LLR computation" processor).

As per **claims 11, 17 and 24**, Ling teaches a wireless receiver (C1, L8-12) and A decoder (C2, L50-67 to C3, L52), responsive to the signal modified by the retrieved scale factor, for decoding a received form of the wireless signal (figure 7 shows the decoder responsive to the LLR)

With further regard to claims 17 and 24, Ling teaches a demodulator (figure 2, #44). The examiner interprets the figures 5-9 as teaching demodulation process being responsive to retrieved values of the scale factor.

With further regard to claim 24, Ling teaches a circuit/processor for computing S/I and LLR (figure 5 and C8, L55-61).

A memory for storing a lookup table (figure 8, #140)

but is silent on

lookup table stores an index retrieves a scale factor is a function of a ratio of energy components of the wireless signal (for claims 11, 17 and 24).

Holtzman teaches using a stored data curve (or plot) which reads on a lookup table (C11, L50-56).

It would have been obvious to one skilled in the art at the time of the invention to modify Ling, such that a lookup table is used for storing scale factor, to provide quicker means of finding the correct/optimal scale factor (ie. lookup versus finding data on a data curve/plot).

As per claims 12, 18 and 25, Ling teaches claim 11/17/24 wherein the signal is a LLR (C2, L50-62).

As per **claims 13 and 19**, Ling teaches claim 11/17 wherein the function is a square root of the ratio between energy components (C14, L4-18 teaches a square root function of Es/Ep and "k" is interpreted to be the scale factor of the LLR).



Art Unit: 2683

As per claims 14, 20 and 26, Ling teaches claim 11/17/24 wherein but is silent on wherein the received signal comprises pilot symbols and data symbols and the ratio between energy components is a ratio between transmitted energy per pilot symbol to a transmitted energy per data symbol.

Ling does teach computing energy per data symbol (\bar{E}_s : C10, L59-60) and pilot symbol energy (E_p : C14, L14-15).

Sampath and Kumar teach β which can be shown to be a ratio of E_p/E_d by rearranging the equation on page 2 (eg. $E_p = \beta E_d$).

Jalloul teaches the calculation of a "pilot to data power ratio" (C5, L26-37).

Holtzman teaches calculating a ratio between the energy of the pilot symbols and the traffic/data channel's energy (C9, L44-46).

It would have been obvious to one skilled in the art at the time of the invention to modify Ling, such that the scale factor is a ratio between energy components, to provide means for correct demodulation (using LLR) based upon a comparison of the energy components of the wireless signal.

As per claims 15, 21 and 27 and 29, Ling teaches claim 11/17/24 and a lookup table (figure 8, #140) but is silent on table values are determined independently of relative strengths and number of mulitpaths in the received wireless signal.

Ling does teach computing the LLR scaling factor which is independent of relative strengths and number of multipaths since the equation does not show variables for these components (C4, L37-67).

Holtzman teaches using a stored data curve (or plot) which reads on a lookup table (C11, L50-56).

It would have been obvious to one skilled in the art at the time of the invention to modify Ling, such that the table values are determined independently of relative strengths and number of mulitpaths in the received wireless signal, to provide means for correct demodulation (using LLR) without requiring dependency on relative strength or number of multipaths.

Art Unit: 2683

As per claims 16 and 23, Ling teaches claim 11/17 wherein the receiver comprises a control signal detector for recovering from the received signal a value for the ratio between the energy per pilot symbol to the energy per data symbol (figures 2 and 4 shows pilot, control and data signals being passed to the "C/I estimation and LLR computation" processor).

As per claim 22, Ling teaches claim 17 further comprising a channel estimator (C3, L63-66).

As per claim 28, Ling teaches claim 24 further comprising a processor for determining scale factor as a function of ratio between energy components of the wireless signal (see claim 1), a noise variance in received data symbols (C4, L22-27) but is silent on a noise variance in received pilot symbols.

Holtzman teaches calculation of the energy per symbol of the traffic channel and determines the estimate of the noise variance (C9, L60-63). Holtzman also teaches (in step 608 of figure 6) the signal and noise estimator estimates the ratio of the energy of the pilot versus the energy of the symbol AND (in step 610) Ep/Es is calculated (C9, L64-67 to C10, L1-7). Holtzman goes on to disclose that other functions and methods may be performed by the signal/noise estimator and control process (C10, L8-16) which reads on calculating a noise variance in received pilot symbols.

It would have been obvious to one skilled in the art at the time of the invention to modify Ling, such that noise variance in received pilot symbols is used, to provide means for incorporating the pilot symbol noise variance into the LLR function.

Art Unit: 2683

Conclusion

Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, THIS ACTION IS MADE FINAL. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Stephen M. D'Agosta whose telephone number is 703-306-5426. The examiner can normally be reached on M-F, 8am to 5pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Bill Trost can be reached on 703-308-5318. The fax phone number for the organization where this application or proceeding is assigned is (703) 872-9306.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is 703-306-0377.

SMD / 2 September 2003

WILLIAM TROST SUPERVISORY PATENT EXAMINER TECHNOLOGY CENTER 2000